

**NORTHWEST PIPE FITTINGS, INC
OF SCOTTSBLUFF, NE**

SEWAGE PUMPS & SUPPLIES



COMPUTER #	DESCRIPTION
519-1949	SKV50AD110 1/2hp SEWAGE PUMP W/DIAPH SWITCH
519-1950	SKV50AW110 1/2hp SEWAGE PUMP W/FLOAT SWITCH
519-4358	W-A1 SUMP PUMP 1/4hp FLOAT TYPE
519-1946	18"X30" ECONO-SEWAGE EJECT BASIN W/LID
519-2450	51752-403-7 DIAPH SWITCH/SP50A F/SKV PUMP
519-2800	12150-026-7 FLOAT SWITCH F/SKV PUMP
519-3681	CV-150 1 1/2"-11/4" CHECK VALVE
519-3542	CV-200 2" CHECK VALVE



SKV

Pump Characteristics

Pump/Motor Unit	Submersible	
	SKV50M1	SKV50M2
Manual Models	SKV50M1	SKV50M2
Automatic Models	SKV50A1	---
Horsepower	1/2	
Full Load Amps	11.0	5.0
Motor Type	Split Phase	
R.P.M.	1750	
Phase Ø	1	
Voltage	115	230
Hertz	60	
Operation	Intermittent	
Temperature	140°F Ambient	
NEMA Design	L	
Insulation	Class B	
Discharge Size	2" NPT std. (3" opt.)	
Solids Handling	2"	
Unit Weight	54 lbs.	
Power Cord	16/3, SJTA, 115V = 10' std. (20' opt.) 230V = 10" std.	

Pump Characteristics

Pump/Motor Unit	Submersible
Automatic Models	W-A1, D-A1 & V-A1
Horsepower	.3
Full Load Amps	8.0
Motor Type	Shaded Pole (4 pole)
R.P.M.	1550
Phase Ø	1
Voltage	115
Hertz	60
Temperature	120°F Ambient
NEMA Design	A
Insulation	Class A
Discharge Size	1-1/2" NPT (38mm)
Solids Handling	1/2" (13mm)
Unit Weight	23 lbs.
Power Cord	18/3, SJTW, 10' std. (20' optional)



W-A1



